

# YEARS AHEAD

## plotWAVE T35

A printer you can build on

Enter the next era of technical drawing and design printing with the plotWAVE T-series. With trusted technology and next-generation printing power, it offers you productive ease of use, IT security features and support for your sustainable business initiatives. Printers you can build on for the years ahead.



### T-series benefits for you

- **Durable printing solution**  
T-series printers are built for reliability and uptime, without the burden of daily maintenance. They are designed to deliver consistent print quality, both over time and on different machines.
- **Professional design philosophy**  
We know how professionals use technical drawings and designs. We designed the T-series for them. For you! Proven Radiant Fusing Technology and easy-to-use intuitive interfaces help users produce first-time-right-prints.
- **Productive ease of use**  
The T-series saves your users time and speeds up your design process. From a quick print to complex jobs and document sets, operation is intuitive even at first glance. Just push the green button! Together with the PRISMA Tech Suite, it's printing you can build on for the years ahead.
- **Streamlined workflow**  
The T-series is designed to fit into your day-to-day processes. Print from applications on Windows or macOS. Submit jobs from mobile devices. Copying and scanning are easy thanks to Image Logic with automatic scan enhancement.
- **IT security features**  
More than ever, you need to protect your IT infrastructure and valuable data assets against unauthorised access. With multiple layers of security features, the plotWAVE T-series is a printer you can build on with peace of mind for the years ahead.
- **Support of your sustainable business initiatives**  
The T-series can help minimise your business footprint. With ENERGY STAR label, Radiant Fusing technology helps reduce energy use. Toner bottles are made of 50% PCR plastics on average. More than 85% of the printer can be reused or recycled.
- **One-stop shop**  
With the plotWAVE T-series, our account professionals help you configure a fully integrated, large-format solution, with hardware, software, supplies and service from a single supplier.

Canon



# TECHNICAL SPECIFICATIONS

STANDARD SYSTEM CONFIGURATION	
1 Roll printing system	Productive large format monochrome printer with ClearConnect multi-touch user panel
Applications	Technical drawings, Maps, POP/POS posters
Stacking systems	Integrated Top Delivery Tray, up to 100 sheets capacity
Multi-touch user interface	ClearConnect multi-touch user interface: Consistent look and feel from every angle of your workflow, standard including Smart Inbox, SmartAccess, printer status and Live Preview
Manual Feed	Manually feed media when the required media type or size is not available on the media rolls or the optional cut sheet tray of the printer
Starter kit (included)	1 bottle toner 500 g, 1 bottle developer 1750 g, 1 roll 36 in standard media 75 g/m2
OPTIONAL SYSTEM CONFIGURATIONS	
Roll media capacity upgrade	Additional 2nd roll option to increase media capacity (200 to 400 m) / 183 to 365 m2)
Office space saving scanning system	Scanner Express with Image Logic technology, integrated CIS scanner positioned on top of the printer to save office space
Removable hard disks	For secure environments, hard disks can be removed from the printer system to secure data integrity
Operator Attention light	For productive environments, the status of the machine is visable from a distance
TECHNOLOGY	
Imaging technology	Electrophotography (LED) with Organic photoconductor (OPC), Clean toner refill system, Virtually no ozone emission
Fusing technology	Radiant Fusing Technology with instant warm-up, contactless fusing, low power consumption (heating on demand)
Automated functions	<ul style="list-style-type: none"><li>Automated print language recognition</li><li>Automated media selection</li><li>Automated media saving function</li><li>Automated media switch</li><li>Pico Printing, intelligent print optimization</li></ul>
Toner	Black toner: 2x500 gram per toner kit. The tonerbottles are made of on average 50% post-consumer recycled plastic
PRODUCTIVITY	
Speed (print and copy)	6 D/AI-sizes <sup>1</sup> per minute; 3 E/A0 sizes <sup>2</sup> per minute
First print out time <sup>3</sup>	<40 seconds
First copy out time <sup>4</sup>	<40 seconds
Print modes	3 print modes
QUALITY	
Print Resolution	600 x 1200 dpi
Minimum line width (ISO/IEC 13660:2001E)	0.06 mm; 0.00236 in
1:1 Line accuracy	< 0.3%
SIZE AND WEIGHT	
Size main engine (WxDxH)	Compact design: 1560 x 803 x 1495 mm; (including Top Delivery Tray and User interface in max pos)
Shipping dimensions (WxDxH)	1470 x 845 x 1260 mm
Weight main engine	220 kg (standard configuration)
Shipping weight main engine	294 kg (standard configuration)
MEDIA HANDLING	
Media capacity	1 or 2 <sup>5</sup> rolls
Media cutting	Automatic cutter included in the drawers for fast and easy roll media switching
Maximum media capacity	1 roll: 200 m1, 183 m2; 2 roll: 400 m1, 365 m2
Media sizes roll	A3, A2, A1, A0, B1, B2, B1-700, B2-700, B, C, D, E, B+, C+, D+, E+, E1, 30 in, 21 in, 15 in, 880 mm, 860 mm, 800 mm, 700 mm, 660 mm, 620 mm, 460 mm, 500 mm, 440 mm, 430 mm, 310 mm, 297 mm
Media sizes manual feed	A3, A2, A1, A0, 11 in, 12 in, 15 in, 17 in, 18 in, 21 in, 22 in, 24 in, 30 in, 34 in, 310 mm, 430mm, 440 mm, 460 mm, 500 mm, 620 mm, 660 mm, 700 mm, 701 mm, 800 mm, 860 mm, 880 mm
Media weight	60 - 110 g/m2; 16 - 29 lb
Roll length	Up to 200 m
Roll width	297 - 914 mm; 11 - 36 in
Roll core diameter	3 in cores. Media loose on core
Minimum printed length	420 mm; 16,5 in
Maximum printed length	200 m; 656 ft

Media type	Plain paper, Plain paper Recycled, Transparencies, Translucent, Recycled paper, Engineering Bond, Engineering Bond Recycled, Engineering Bond Translucent, Engineering Vellum, Coloured paper, Top Label Paper FSC, Top Colour Paper FSC, Red Label Paper PEFC, Red Label Zero FSC, RecycledWhiteZero FSC, Transparent Paper, Transparent Paper FSC, Polyester film, Polyester film antistatic, Contrast Film, Clear Polyester Film, Double Matte Polyester Film, White Opaque Polyester Film, Orika LPEX rice paper
Media type manual feed	Plain paper, Recycled paper, and Coloured paper, films and transparent media
Automatic roll media handling	<ul style="list-style-type: none"><li>Automatic width detection</li><li>Automatic roll media selection for optimised productivity and media saving, based on drawing size, media type, roll width and finishing</li><li>Automatic roll switching when end of roll is reached</li><li>Automated media switch, to guide the media to the top delivery tray or back output depending on the user application</li></ul>
ClearConnect USER INTERFACE	
Description	ClearConnect multi-touch user panel
Size (WxHxD)	300 x 220 x 40 mm; 11.8 x 8.7 x 1.6 in (10.4 in at 4x3 ratio)
Resolution	800 x 600 pixels (SVGA)
Number of colours	16.2 Million
Technology	Projective capacitive touch
Operation	3 hard buttons: [Wake-up], [Stop, interrupt, abort], [Home] Multi-touch functions: tap, double tap, pinch, 2 finger pinch, swipe, flick and spread
Interface design	Distinctive user interface with intuitive navigation and clearly defined levels of operation
Features	View optimisation: Tilt (-4 to +45 degrees) and turn (-45 to +180 degrees) Status light (red, orange, green) USB 2.0 interface with indication light. Switch instantly between 2 languages, select from 19 languages; Czech, Danish, German, English, Spanish, Finnish, French, Hungarian, Italian, Japanese, Korean, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Chinese simplified, Chinese-traditional
CONTROLLER	
Description	High performance POWERsync <sup>®</sup> controller with Windows 10 IoT Enterprise LTSC 2021, 64 bits
Processor	6 Core, 6 Thread, Core i5-8500 @4.10GHz
Memory	2x8 GB DDR4
Video	Intel UHD Graphics 630, 1,1GHz
Hard Disk	2x 500 GB, 7200 rpm (standard)
TPM	TPM 2.0
Interface	2x Ethernet 100 Mbits/s, 1 Gbit/s TCP/IP: DHCP, IPv4, IPv6, HTTPS Discovery; APIPA, WS-Discovery, SNMP WAVE interface
Page description language	TIFF, JPEG, HPGL, HPGL2, DWF, C4, Calcomp 906/907/951, CALS, NIRS/NIFF
Page description language (optional)	PS/PDF license provides access to Adobe PostScript 3 and PDF1.7. It enables the Adobe CPSI 7.10 (Configurable PostScript Interpreter).
Printing protocol	<ul style="list-style-type: none"><li>LPR, FTP, WebDav</li><li>FTP</li><li>Pull from SMB, FTP</li><li>Pull from cloud (retrieve from ARC Collaborate, WebDAV based clouds)</li><li>HTTP/HTTPS (used by Publisher Express and PRISMAproduce Tech)</li><li>Print from home folder (via access management license)</li></ul>
Back Channel protocol	HTTP or HTTPS
Transformations	Scaling (scale-to-fit page, reduce when image too large to avoid clipping or to custom factor, scale page size to standard size), Rotation, Shift (automatic or user defined), Adding/removing trailing/leading edge, Mirror, Black intensity in poster mode, Print optimisation (standard, lines/text, poster). Colour Highlight and Dark Original. Area to erase (area of interest)
Cloud support	Cloud support via the WebDav protocol or via 3th party providers like uniFLOW <sup>®</sup> . The cloud user authentication can either be preconfigured by the administrator or done by the user at the time of accessing the specific cloud.

SMARTshield INTEGRATED SECURITY	
Safe submission	Access Control (IP filtering), IPSec, HTTPS, IP4 and IP6 compatible, password data protection
Safe storage and removal	Secure file erase, E-shredding, Secure boot, Data encryption with Embedded FIPS 140-2 Certified Trusted Platform Module 2 (TPM), BitLocker 256 AES encryption, Optional Removable hard disks and optional HDD's destruction at the end of the contract.
Authorisation	User authentication for access on the ClearConnect user panel/ WebTools Express (via LDAP/Active Directory credentials and optional via Access card), Print file protection via pincode or password, Possible to disable ports and interfaces, Standard uniFLOW embedded applet installed on the controller, for integration in uniFLOW please contact your Canon representative.
Hack prevention	IEEE 802.1x Authentication, SNMP v3, Audit logging, Configure HTTPS Certificates. TLS 1.2 strong cipher (Possible to disable TLS1.0 and 1.1 protocols), Possible to disable unused protocols, Security Event Logging, Optional Trellix antivirus software, Optional Trellix Application Control (whitelisting)
Secure now and in the future	Windows 10 Enterprise LTSC 2021 controller operating system with Microsoft security patches up to 2032. SMARTshield CIP (Continuous Improvement Process) including: Automatic Microsoft security patch update services with notifications and scheduling, Continuous monitoring of vulnerabilities by Canon ( <a href="https://psirt.canon">https://psirt.canon</a> ), Annual external security audit program based on the OWASP top 10 methology ( <a href="https://owasp.org">https://owasp.org</a> ), Monitoring of new legislation and - high impact breaches.
SCANNER EXPRESS (optional)	
Description	Integrated Contact Image Sensor (CIS) Colour scanner with Image Logic technology
Scan resolution	600 x 600 dpi
Scan speed	15.2 m/min Black & white scanning 5.0 m/min Colour scanning
Scan formats	TIFF, PDF, PDF/A, JPEG, CALS, multi-page PDF, multi-page PDF/A and multi-page TIFF
Scan templates	Extensive number of scan templates to standardise common scan settings and destinations
Scan protocol	FTP, SMB, scan to cloud (push to WebDAV based clouds)
Scan destination	Local USB flash drive, FTP, SMB, Smart Inbox on Controller, Optional Local Home folder (LDAP), mobile device via WebTools Mobile, WebDAV Clouds
Scan naming	Preset naming with auto numbering for productive scanning or file name on the ClearConnect user panel
Original width	208 mm - 965 mm; 8.2 in - 38 in, automatic width detection
Original length	208 mm - 16000 mm; 8.2 in - 630 in, automatic length detection
Effective scan width	932 mm
Original thickness	Maximum 0.8 mm; 0.03 in (non-rigid documents)
Zoom (copy)	1:1, Scale to media size, Scale to standard format, Custom: 10 - 1000%
Original types presets	Blueprint, Coloured original, Dark original, Folded lines/text, Lines/text standard, Lines/text draft, Photo, Map, Artwork
Size scanner (WxDxH)	1097 x 308 x 140 mm; 43 x 12 x 5.5 in
Weight scanner	25 kg; 55 lbs
ENVIRONMENTAL	
Sound power level	Standby and sleep: 4.2 B(A) Print mode: 7.0 B(A)
Sound pressure level	Standby and sleep: 24 dB Print mode: 58 dB
Ozone concentration	0.42 mg/h <0.001 mg/m3
Heat emission	Ready: 71W; Active: 1.6 kW
Operating temperature	Optimal print quality in temperature range 20 - 27 °C (68 - 81 °F)
Operating humidity	Optimal print quality in humidity range 30 - 60% RH
Power requirements	100 - 240 V; 50/60Hz
Power consumption	Sleep mode: <2 W Ready mode: 64 W Active mode: 1547 W
Safety/EMC marks & environmental labels	CE, TÜV GS, cetecom advanced, c-UL-US, CB, RCM, ENERGY STAR 3.0, FEMP, EPEAT, CCC, EAC, FCC Class A, VCCI Class A, RoHS
Earthquake provision <sup>7</sup>	Secure the printer preventing moving or tilting during an earthquake. This provision enables the user to secure the printer to a sturdy connection of the building
Recyclables	Printer: made of steel or highly recyclable plastics: up to 95% of the engine can either be up cycled or recycled. Remaining 5% are non toxic waste. Prints: Deinkability certificate Toner: Toner bottles made from on average 50% recycled HDPE (High Density Polyethylene)
Second life program	Compatibility with selected legacy scanners and stackers

WORKFLOW SOFTWARE	
PRISMAtech Suite	Create breathtaking applications while staying in control of your printer with powerful workflow solutions that are designed to help you with your day to day print operation.
PRISMAproduce Tech	Compose, manage and submit complex sets of documents from your web browser to one or more printers at a time.
PRISMAlytics Dashboard	Get comprehensive overviews to monitor and maximise the production of your print operations with this secure cloud-based management information tool.
PRISMAlytics Accounting	Capture data for cost charging and usage monitoring with this cloud-based reporting tool.
PRISMAservice	Maximise your uptime with our CARE methodology: Collect data remotely, Analyze the data, Repair printers via remote assistance and Evaluate for continuous improvement.
DRIVERS, SUBMITTERS, USER PANEL	
Drivers	Easy to use printer drivers that allow you to effectively and efficiently print from any application. Create, retrieve and/or send jobs from: <ul style="list-style-type: none"><li>Driver Select for Microsoft Windows</li><li>Driver Express for Adobe PostScript 3 for Microsoft Windows or Apple OS</li></ul>
Job submission	<ul style="list-style-type: none"><li>Publisher Mobile - Submit print jobs via your mobile phone app supporting IOS and Android</li><li>Publisher Express - Easily submit your print jobs via the web independent of your web browser</li></ul>
ClearConnect User Panel	Print, Copy, Scan is as easy as using a tablet with the multi-touch user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors
CONTROLLER WORKFLOW	
Open architecture	Integrate smoothly into print management applications such as uniFLOW thanks to our POWERsync <sup>®</sup> controller
Smart inbox	Personalised Smart Inbox with history, manage queue, manage history, WebTools Express, secured controller access
Queue management	Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Customise priority settings for copy and print jobs in the queue. The Job Queue overview gives access to job names, owners and status including required media. Jobs can be paused, deleted, and placed on top of the queue
Print management	View the counter history at preferred time periods, per job or total overview in WebTools Express. View, create, edit and delete stamp templates. Standard uniFLOW support installed on controller, login your personal uniFLOW Queue on the ClearConnect User interface. Supports accounting, manual authentication, card readers, and contactless card readers. Scan to email and scan to cloud is supported.
Mobile and cloud	Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile the printer can be easily accessed and used from any location
Device management	WebTools Express provide administrators the tools to manage the device remotely via the web: e.g. check printer status, Remote ON function, ink/toner status, define default settings for print, copy and scan, define access, security, accounting, remote shutdown, software update and restart, power on/off timer, system behaviour, queue management, license management, view, create, edit and delete stamp templates etc
PERIPHERALS (optional)	Folder Express 3000, Stacker Select, Scanner Professional II.
FOOTNOTES:	
1	D size (34 x 22 in) / A1 size (841 x 594 mm)
2	E-size (36 x 48 in) / A0 Size (841 x 1189 mm)
3	1 A1 landscape print made from the smart inbox, on 64 g media, back output, lines and text mode
4	1 copy made with A1 original in landscape on 64 g media, back output, background compensation off, custom width 841 mm, custom length 594 mm
5	Optional
6	Based on current third party support
7	Excluding cable/chain and mounting material

# PLOTWAVE T35

Adobe and Postscript are either registered trademarks or trademarks of Adobe Systems Inc. in the United States and/or other countries; Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries; iOS is a registered trademark or trademark of Apple Inc. in the United States and/or other countries

No part of this publication may be copied, modified, reproduced or transmitted in any form or by any means, electronic, manual, or otherwise, without the prior written permission of Canon Production Printing. Illustrations and printer output images are simulated and do not necessarily apply to products and services offered in each local market. The content of this publication should neither be construed as any representation, guarantee or warranty with regard to specific properties or specifications nor of technical performance or suitability for particular applications. The content of this publication may be subject to changes from time to time without notice.

© 2024 Canon Production Printing  
Canon is a registered trademark of Canon Inc.  
plotWAVE and PRISMA are a registered trademark of Canon Production Printing Netherlands B.V.



Canon Production Printing  
cpp.canon  
English edition