

## XL-3610 2D BARCODE SCANNER



- Unique appearance, stylish shape, modern design
- 0.3 million global shutter camera, fast reading speed 60fps/s
- Fast reading on all 1D/2D barcode on paper and screen
- Quick decoding 3mil barcode and difficult barcodes  
(blurred, wrinkled, low contrast, high density, high accuracy, long barcode)
- Compatible with Windows 7/8/10, iOS, Android, Linux system
- Suitable for retail stores, supermarkets, restaurant, pharmacy



### THE PERFORMANCE PARAMETERS

Image Sensor	CMOS
Light Levels	White LED (Lighting) RED aiming light
CPU	32bit ARM
Exposure	Global Shutter
Image size	640x480 pixels
Scanning speed	60fps
Decoding Depth	60-360mm (13mil PCS90%)
Minmum Resolution	3mil
Interface	USB-HID, USB-VCP, RS232
Scan Mode	Manual& Automatic
Materials	ABS+TPU
Size	L*W*H : 163*68*80(mm)
Weight	185g
Input Voltage	DC 3.6V-5.5V
Working current	142mah
Stand-by current	42mah
Temperature(Operating)	-10°C — 50°C
Temperature(Storage)	-20°C — 60°C
Indicate	LED Indicator and Buzzer
Cable Standard	1.5m
Motion Tolerance	13cm/ second, (Skew/Pitch) +/- 65°; +/- 65°
Humidity	5%— 95%(non-condensing)
Light Source	0 — 5000Lux(fluorescent light), 0—100,000Lux(daylight)
Print min. Contrast	10%
IP Class	IP54
Decoding Capability	1D: Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, etc. 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code

### SUNLUX IOT TECHNOLOGY ( GUANGDONG ) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China  
 Tel: +86-20-32053765 Fax: +86-20-82115390  
 Site: [www.xl-scan.com](http://www.xl-scan.com)  
 E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)

