

# Industrial Wireless Scanner

## XL-9529



- ⊙ Support 1D/2D
- ⊙ Wireless inductive charge without cable
- ⊙ IP65 ; Unique industrial drop resistance design
- ⊙ 600M Communication distance in open places
- ⊙ With memory card inserted in scanner and can store 100000 EAN-13 barcode



Light Source	Red Light, LED, 625nm±10nm	Size	L × W × H:186mm × 66mm × 108mm
Scan Pattern	Single Scan & Manual & Continuous	Charge Mode	Wireless charging
Working Frequency	433 MHz ISM frequency	Weight	879.8g
Communication Distance	Up to 600m at open places	Material	ABS+PC
Scan Precision	4mil	Voltage	2200 mAh/DC 12V
Depth of Scan Field	50-260mm(EAN-13,13mil) 60-285mm(PDF417,15mil)	Operating Current	300mA/35mA
Scan Angle	30° & 65° & 55°	EMC	CE & FCC DOC compliance
Support Interface	RS232, PS2 and USB	Operating Temperature	- 20°C to 50°C
Print Contrast	15% UPC/EAN 100%	Storage Temperature	- 20°C to 60°C
Mention Pattern	Buzzer, Indicator	Humidity	5% to 95% relative humidity
Cable	Standard 2M straight	Shock	2M drops
Decoding Capability	1D : Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN/ISSN, Code 93, UCC/EAN-128, GS1 Databar 2D : PDF417, QR Code, DataMatrix		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)