contex ScanStation

Boost your scan, copy and archiving productivity. Optimized for scanning service professionals

ScanStation^{Pro} The professional's scanner



ScanStation^{Pro}

Get the best out of all your originals.



Your full, open system

Scanner, 21.5" full HD touchscreen, Nextimage REPRO software, height-adjustable stand, PC basket and keyboard tray. Simply add your choice of PC.







Ideal as a standalone scanning solution, or combined with your preferred printers Flexible configurations to place alongside your printer, or save space with a high stand above your

The ultimate scanning experience

ScanStation^{Pro} is the most efficient way to scan, copy, file, or archive any wide-format document. Scan faster, up to 626 documents per hour, so you can take on more jobs.

Unique technology, which speeds up your process by more than 30%, increases efficiency and decreases your operating costs.

Works with your IT infrastructure

Suitable for all environments, you can pair this with the computer of your choice to easily integrate into your company's IT infrastructure.

Includes award winning software

Designed specifically for fast batch


















The fully-featured touchscreen offers all, zoom, pinch, and swine functions





IQ Quattro 4450 ScanStation ^{Pro}	IQ Quattro 4490 ScanStation ^{Pro}	HD Ultra i4250s ScanStation ^{Pro}	HD Ultra i4290s ScanStation ^{Pro}	HD 5450 PLUS ScanStation ^{Pro}		
Scanning Speed (inch/sec.): Scanner speed while scanning 36-inch wide document.						
7 ips 200 dpi	14 ips 200 dpi	4 ips 200 dpi	8 ips 200 dpi	3 ips 400 dpi (Turbo)		
Yes. To 14 ips	-	Yes. To 8 ips	-	-		
14 ips 200 dpi	14 ips 200 dpi	12 ips 200 dpi	12 ips 200 dpi	12 ips 400 dpi (Turbo)		
	ScanStation ^{Pro} er speed while scanning 36-i 7 ips 200 dpi Yes. To 14 ips	ScanStation ^{Pro} ScanStation ^{Pro} er speed while scanning 36-inch wide document. 7 ips 200 dpi 14 ips 200 dpi Yes. To 14 ips	ScanStation ^{Pro} ScanStation ^{Pro} ScanStation ^{Pro} er speed while scanning 36-inch wide document. 7 ips 200 dpi 14 ips 200 dpi 4 ips 200 dpi Yes. To 14 ips - Yes. To 8 ips	ScanStation ^{Pro} ScanStation ^{Pro} ScanStation ^{Pro} ScanStation ^{Pro} er speed while scanning 36-inch wide document. 7 ips 200 dpi 14 ips 200 dpi 4 ips 200 dpi 8 ips 200 dpi Yes. To 14 ips - Yes. To 8 ips -		

Productivity (documents/hour): Batch scanning for 60 minutes. Includes paper load and eject time. Measured in completed scans:

Arch E-size, RGB Color, 200dpi 626 302 455 258 394

ScanStationPro:

ocanotation .				
REimage by Contex	Virtually rescan documents directly in Nextimage REPRO			
Display and Touch	21.5" Widescreen HD TFT LCD, 1920x1080 dpi			
Connnectivity	2 x Gb Ethernet / 4 x USB 3.0 and 1 x USB 2.0			
Maximum Scan Width	44 inch (1118 mm)	42 inch (1067mm)	54 inch (1372 mm)	
Maximum Media Width	47 inch (1194 mm)	44 inch (1120 mm)	56 inch (1422 mm)	
Optical Resolution	1200 dpi	1200 dpi	508 dpi	
Maximum Resolution	9600 dpi	9600 dpi	9600 dpi	
Technology	Contex CleanScan CIS	5 x 4 linear color CCDs (R,G,B and Gray)	4 x 4 linear color CCDs (R,G,B and Gray)	
Maximum Media Thickness	0.08 inch (2 mm)	0.6 inch (15 mm)	0.6 inch (15 mm)	
Accuracy	0.1% +/- 1 pixel			
Data Capture ¹ (color/mono)	48-bit / 16-bit			
Color Space	Adobe RGB / Device RGB / RAW RGB / sRGB	Adobe RGB / Device RGB / RAW RGB / sRGB	sRGB	
USB	USB and Gigabit Ethernet with xDTR2	USB and Gigabit Ethernet with xDTR2	USB	
Gigabit Ethernet with xDTR2	•	•	-	
Energy Star Certified	•	•	-	

Adjustable stand and touchscreen:

ScanStation 21.5" Touch Screen 21.5" Multi Touch Widescreen. Full HD TFT LCD, 1920x1080 dpi

(135.0 x 48.0 x 16.1 cm)

Screen Mounting Optional. Left or right side

36.0 / 37.0 / 38.0 inch Low Stand: Working Height 32.8 / 33.8 / 34.8 inch (834 / 859 / 884 mm) 36.3 / 37.3 / 38.3 inch (922 / 947 / 972 mm) (915 / 940 / 965 mm) High Stand: 995 to 1195 mm in 25 mm increments (39.2 to 47inches in about 1 inch increments) Not Available Supported Printer Height

Full Featured Nextimage4 Repro Software Included:

Language versions	Chinese, Dutch, English, French, German, Italian, Japanese, Korean, Polish, Russian, Spanish			
Operating system	32 and 64-bit Windows 10, 8, 7 and Vista			
NextImage TWAIN	32-bit TWAIN application driver included for use with EDM and other imaging software			
File formats	TIF, JPG, PDF, PDF/A, DWF, CALS, BMP, JPEG-2000(JP2), JPEG2000 Extended(JPX), TIF-G3, TIF-G4, others			
Auto Naming Templates	Configurable Counters, Date, Time and other. Use in folder and filenames or both			
Software ²	AutoCAD®, Microstation tm , ArcGIS tm and all other CAD, GIS and other image editing / storage applications			
Power Requirements	100-240V, 60/50Hz, 80W	100-240V, 60/50Hz, 80W	100-240V, 60/50Hz, 180w	
Scanner Weight & Dimensions	27 kg, LxWxH: 53.1 x 18.9 x 6.3 inches	48 kg, LxWxH: 52.8 x 18.7 x 7.9 inches	79 kg, LxWxH: 67 x 19 x 7	

1 Bit depth for: Data Capture / Scanner Processing / PC Processing / Image File. Create an optional 48-bit TIFF image

2 Contex applications create industry standard raster file formats that can be used in any CAD or GIS application.

All trademarks remain the property of their respective holders, and are used only to directly describe the product being provided. Their use in no way indicates any relationship between Contex A/S and the holders of the said trademarks.

(134 x 47.5 x 20 cm)

The professional's solution



Scanner Weight & Dimensions

ScanStationPro

- IQ Quattro 4450 - IQ Quattro 4490



ScanStationPro

- HD Ultra i4250s - HD Ultra i4290s



Nextimage Software for scanning, copying and printing.



Height adjustable stand for optimal ergonomics

Contex Head Office Phone: +45 4814 1122 info@contex.com

inches (169 x 47 x 18 cm)









For a full list, see www.contex.com





Contex solutions work with all leading large-format printers.