


# For that moving target called growth.

Keep building your business with the compact, yet versatile TASKalfa 308ci and TASKalfa 358ci. Ideal for small to mid-size businesses, these multifunction printers grow with you as your needs evolve. You'll appreciate the intuitive 7" Color Touch Screen with tablet-like functionality that makes it easy to find features and interact with business apps. No matter what your needs are and how they change, these intelligent systems will be there for you today and tomorrow.



<b>TASKalfa 308ci / 358ci Series</b> 
<b>Up to 32 / 37 Pages per Minute</b>
<b>Professional Finishing Options</b>
<b>HyPAS-enabled for Solutions &amp; Apps</b>
<b>KYOCERA Document Manager Ready</b>

# The TASKalfa 308ci / 358ci Series Options



Only available for the TASKalfa 358ci model  
 Available for both the TASKalfa 308ci and 358ci models  
<sup>1</sup> Requires AK-5100  
<sup>2</sup> Requires PF-5100

# General Specifications



## TASKalfa 358ci

### Pages Per Minute:

Color and Black – Letter: 37 ppm, Legal: 30 ppm, A4: 35 ppm

**Warm Up Time:** 24 Seconds or Less (Power On)

### First Page Out:

Copy: 5.9 Seconds or Less Black, 7.3 Seconds or Less Color;

Print: 5.5 Seconds or Less Black, 6.5 Seconds or Less Color

### Typical Electricity Consumption (TEC):

120V: 1.86 kWh / week;

220V: 1.66 kWh / week

**Weight:** 104.5 lbs (excludes Optional Document Processor)

**Maximum Monthly Duty Cycle:** 100,000 Pages per Month

### Basic Specifications

**Display:** New 7" 800 x 480 dot Color Touch Screen Control Panel

**Resolution:** 600 x 600 dpi; 1200 x 1200 dpi

(At reduced speed)

**Memory:** 4GB Standard

**Hard Disk Drive:** 320GB HDD Standard

**Standard Output Tray:** Statement - Legal / 500 sheets; up to

8.5" x 48" Banner / Single Sheet

**Electrical Requirements:** 120V, 60Hz, 8.9A; 220-240V, 50Hz, 5.4A

**Dimensions:** 21.65" W x 19.96" D x 29.13" H

### Print Specifications

**Standard Controller:** Freescale QorIQ T1024 / 1.0GHz

**PDLs / Emulations:** PRESCRIBE, PCL6 (PCL-XL / PCL5c), KPDL3 (PS3), XPS, OPEN XPS;

**Optional (UG-34):** IBM ProPrinter, Line Printer, LQ-850

**Print Resolution:** Up to 1200 x 1200 dpi (At reduced speed)

**Interfaces:** Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 3 USB

Host Interfaces, 2 Expansion Slots

### Scan Specifications

**Scan Speeds (mono/color) @ 300 dpi:**

**DP-5100:** Simplex: 60, 62 ipm BW / 60, 62 ipm Color;

Duplex: 26, 27 ipm BW / 26, 27 ipm Color

**DP-5120:** Simplex: 60, 62 ipm BW / 60, 62 ipm Color;

Duplex: 120, 124 ipm BW / 120, 124 ipm Color

**DP-5130:** Simplex: 85, 87 ipm BW / 65, 67 ipm Color;

Duplex: 170, 174 ipm BW / 130, 134 ipm Color

### Copy Specifications

**Job Management:** 1,000 Department Codes

### Optional Document Processors

**Type / Capacity:**

**DP-5100<sup>2</sup>:** Reversing Automatic Document Processor / 75 Sheets

**DP-5120<sup>2</sup>:** Dual Scan Document Processor / 100 Sheets

**DP-5130<sup>2</sup>:** Dual Scan Document Processor / 270 Sheets

**Acceptable Originals:** 5.5" x 8.5" – 8.5" x 74.8" (1900mm)

**Acceptable Weights:**

**DP-5100:**

Simplex: 13 – 32 lb Bond (50 – 120gsm);

Duplex: 13 – 32 lb Bond (50 – 120gsm)

**DP-5120:**

Simplex: 13 – 32 lb Bond (50 – 120gsm);

Duplex: 13 – 32 lb Bond (50 – 120gsm)

**DP-5130:**

Simplex: 13 – 32 lb Bond (50 – 120gsm);

Duplex: 13 – 32 lb Bond (50 – 120gsm)

### Optional Fax Processors

**Fax Type:** Fax System 10(X)

**Fax Memory:** Standard 170 MB (No scalability: Maximum 170 MB)

### Optional 1,000 Sheet Finisher DF-5110<sup>3,4</sup>

**Stack / Staple Capacity:**

**Main Tray:** 1,000 Sheets (up to 80gsm) / 50 Sheets

(up to 24 lb Bond [90gsm])

**Paper Size:** 5.5" x 8.5" – 8.5" x 14"

**Paper Weight:** 16 lb Bond – 120 lb Index (60 – 220gsm)

**Edge Staple Position:** 3 Positions: Top Left, Bottom Left, Center Bind

**Optional Punch:** PH-5100 2 and 3 Hole Punch Unit,

Supports 5.5" x 8.5" – 8.5" x 14"; 16 lb Bond – 120 lb Index

(60 – 220gsm)

**Dimensions:** 23.27" W x 20.35" D x 39.58" H

### Optional 3,200 Sheet Finisher DF-5120<sup>3,4</sup>

**Stack / Staple Capacity:** Main Tray (A): 3,000 Sheets; Sub Tray (B):

200 Sheets / 50 Sheets

**Paper Size:** 5.5" x 8.5" – 8.5" x 14"

**Paper Weight:** 16 lb Bond – 120 lb Index (60 – 220gsm)

**Edge Staple Position:** 3 Positions: Top Left, Bottom Left, Center Bind

**Standard Punch:** PH-5100 2 and 3 Hole Punch Unit,

Supports 5.5" x 8.5" – 8.5" x 14"; 16 lb Bond – 120 lb Index

(60 – 220gsm)

**Dimensions:** 25.59" W x 20.94" D x 42.35" H

### Additional Options

Bridge Unit Attachment Kit (AK-5100), Job Separator3 (JS-5100),

Internet Fax Kit (A), Card Authentication Kit (B), ThinPrint (UG-33),

Emulation (UG-34), Document Tray (DT-5100), Scan Extension Kit (A)

for Searchable PDF/OCR, Key Counter, Key Counter Attachment Kit,

Card Reader Holder (11), 5 Bin Mailbox (MT-5100), Wireless Card IB-50,

Wireless Card IB-51

## TASKalfa 308ci

### Pages Per Minute:

Color and Black – Letter: 32 ppm, Legal: 26 ppm, A4: 30 ppm

**Warm Up Time:** 20 Seconds or Less (Power On)

### First Page Out:

Copy: 6.4 Seconds or Less Black, 7.8 Seconds or Less Color;

Print: 7.0 Seconds or Less Black, 8.0 Seconds or Less Color

### Typical Electricity Consumption (TEC):

120V: 1.55 kWh/week;

220V: 1.43 kWh/week

**Weight:** 109.3 lbs (includes Standard RADF)

**Maximum Monthly Duty Cycle:** 100,000 Pages per Month

### Basic Specifications

**Display:** 7" Color Touch Screen Control Panel

**Resolution:** 600 x 600 dpi; 1200 x 1200 dpi

(At reduced speed)

**Memory:** 1.5GB Standard (3GB Maximum)

**Hard Disk Drive:** Optional 32GB (HD-6) or 128GB (HD-7) SSD

**Standard Output Tray:** Statement - Legal / 500 Sheets

**Electrical Requirements:** 120V, 60Hz, 8.5A; 220-240V, 50Hz, 5.3A

**Dimensions:** 21.65" W x 19.96" D x 29" H (includes RADF)

### Print Specifications

**Standard Controller:** Main: SoC (PPC4655) 1GHz

**PDLs / Emulations:** PRESCRIBE, PCL6 (PCL-XL/PCL5c), KPDL3 (PS3),

XPS, OPEN XPS

**Print Resolution:** Up to 1200 x 1200 dpi (At reduced speed)

**Interfaces:** Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 2 USB

Host Interfaces, 2 Expansion Slots

### Scan Specifications

**Scan Speeds (mono/color) @ 300 dpi:**

**STD:** Simplex: 40, 42 ipm BW / 30, 32 ipm Color;

Duplex: 17, 18 ipm BW / 13 ipm Color

### Copy Specifications

**Job Management:** 100 Department Codes

### Standard Document Processor

**Type / Capacity:** Standard Reversing Automatic Document Processor

/ 75 Sheets

**Acceptable Originals:** 5.5" x 8.5" – 8.5" x 36" (915mm)

**Acceptable Weights:** Simplex: 13 – 32 lb Bond (50 – 120gsm);

Duplex: 13 – 32 lb Bond (50 – 120gsm)

### Optional Fax Processors

**Fax Type:** Fax System 11

**Fax Memory:** 3.5 MB

### Additional Options

Bridge Unit Attachment Kit (AK-5100), Job Separator2 (JS-5100), Card

Authentication Kit (B), Gigabit NIC (IB-50), IEEE802.11b/g/n (IB-51),

ThinPrint (UG-33), Document Tray (DT-5100), Card Reader Holder (11),

SD Card<sup>4</sup> (16 or 32GB), 5 Bin Mailbox (MT-5100), Scan Extension Kit,

Wireless Card IB-55





The TASKalfa 308ci/358ci are compact, highly scalable, multifunction systems that streamline your document processing. A host of intelligent features boost productivity, from robust paper handling and advanced finishing to a standard security kit.

## Specifications

### Basic Specifications

**Configuration:** Color Multifunctional System – Print/Scan/Copy/Optional Fax

**Duplex:** Standard Stackless Duplex Supports Statement to Legal (5.5" x 8.5" – 8.5" x 14"), 16 lb Bond – 120 lb Index (60 – 220gsm)

### Security Specifications

**Standard:** Local Authentication, Network Authentication, IPsec, SNMPv3, IEEE802.1x, IPP over SSL/TLS, HTTPS, FTP over SSL/TLS, SMTP over SSL/TLS, POP3 over SSL/TLS, Enhanced WSD over SSL/TLS, LDAP over SSL/TLS

**Data Security Function:** HDD Overwrite Mode, HDD Data Encryption

### Print Specifications

**Fonts:** 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap

**OS Compatibility:** Windows: 7/8/8.1/Server 2003/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2

**Mac:** OS Compatibility: Mac OS 10.5 and later, AirPrint Enabled

**Mobile Printing:** Apple AirPrint®, Google Cloud Print™, Mopria®, KYOCERA Mobile Print

Optional: 10/100/1000BaseTX (IB-50 for Dual NIC);

Optional: IEEE 802.11 b/g/n (IB-51 for Wireless LAN Interface)

Optional: IEEE 802.11 b/g/n (IB-35 for Wireless LAN Interface) for 308ci / (358ci comes standard with IB-35)

**Network Print and Supported Protocols:** TCP/IP, IPv4, IPv6; HTTP, LPD, FTP, IPP, RawPort, LLTD, SNMP, DHCP, SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print

**Drivers:** KX Driver, PCL Mini Driver, KPDL Mini Driver, KX Driver for XPS, Network Fax Driver, TWAIN Driver, WIA Driver, PPD for MAC, PPD for Linux

**Utilities:** KYOCERA Device Manager, KYOCERA Net Viewer, KYOCERA Capture Manager, Command Center RX

### Paper Supply

**Standard Paper Sources:** Single 500 Sheet Tray, 100 Sheet MPT

**Optional Paper Sources:**

500 Sheet Tray (PF-5120), Dual 500 Sheet Trays (PF-5130); 2,000 Sheet Large Capacity Tray (PF-5140)<sup>1</sup>

**Paper Capacity:** Standard: 600 Sheets; Maximum: 3,100 Sheets

**Paper Size:**

Tray 1 – PF-5120 and PF-5130: 5.5" x 8.5" – 8.5" x 14" (Statement to Legal); PF-5140: 8.5" x 11" (Multiple Sheets) MPT: 5.5" x 8.5" – 8.5" x 14" (up to 356mm for 308ci Multiple Sheets / up to 1220mm for 358ci Single Sheet)

**Paper Weight:** Trays/MPT: 16 lb Bond – 120 lb index (60 – 220gsm)

**Input Materials:** Standard/Optional Drawer: Plain Paper, Bond Paper, Recycled Paper, Envelopes; MPT: Plain Paper, Bond Paper, Recycled Paper, Cardstock, Transparencies, Labels, Envelopes

### Scan Specifications

**File Formats:** TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG

**PDF Extension:** Searchable PDF (OCR) Option

**Connectivity / Supported Protocols:**

10/100/1000BaseTX, TCP/IP, Hi-Speed USB 2.0

**Scanning Functions:** Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

**Original Size:**

Through DP: Statement to Banner (5.5" x 8.5" – 8.5" x 74.8" for 358ci, up to 915mm for 308ci); Glass: up to 8.5" x 14"

### Copy Specifications

**Copy Resolution:** 600 x 600 dpi

**Image Mode:** Text, Photo, Text/Photo, Graphic/Map

**Continuous Copy:** 1 – 999 / Auto Reset to 1(308ci) 1 – 9999 / Auto Reset to 1(358ci)

**Additional Features:** Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Interrupt Copy

**Magnification / Zoom:** Full Size, 7 Reduction, 5 Enlargement (for 308ci/358ci 5RSE) Preset Ratios, 25-400% in 1% step increments

**Document Box:** Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

### Optional Fax Specifications

**Compatibility / Data Compression:**

Super G3 Fax / MMR, MR, MH, JBIG

**Transmission Speed / Modem Speed:**

Less than 3 seconds / 33.6 Kbps

**Driver:** Network Fax Driver

**Fax Functions:** Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

## Output & Finishing Options

### Optional 300 Sheet Inserter DF-5100<sup>3</sup>

**Stack / Staple Capacity:**

300 Sheets / 50 Sheets (up to 24 lb Bond [80gsm])

**Paper Size:** 5.5" x 8.5" – 8.5" x 14"

**Paper Weight:** 16 lb Bond – 120 lb Index (60 – 220gsm)

**Edge Staple Position:** 3 Positions: Front 1 staple, Edge 1 staple, Face 2 staple

**Dimensions:** 19.13" W x 15.55" D x 6.22" H

<sup>1</sup>Requires PF-5120

<sup>2</sup>Only 1 Document Processor can be installed

<sup>3</sup>Only 1 output option can be installed

<sup>4</sup>Requires Bridge Unit Attachment Kit (AK-5100)



Specifications and design are subject to change without notice. For the latest on connectivity visit [usa.kyoceradocumentsolutions.com](http://usa.kyoceradocumentsolutions.com). TASKalfa, KYOCERA Document Manager, and Command Center RX are trademarks of the Kyocera Companies. AirPrint is a trademark of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. Mopria is a trademark of Mopria Alliance, Inc. All other trademarks are the property of their respective owners.